THE NETHERLANDS



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning the:

- type-approval

- extension-of-type-approval

- refusal-of-type-approval

- withdrawal-of-type-approval

of a type of component (towing bracket) with regard to Directive 94/20/EC

Type-approval number: e4*94/20*0129*00

Reason for extension:

SECTION I

0.1 Make (trade name of manufacturer) : Bosal

0.2. Type and general commercial description(s) : 021291

0.3. Means of identification of type if marked on the component : Approval number

0.3.1 Location of the marking : on type plate

0.3.1. Location of the marking : on type pla

0.5. Name and address of manufacturer : Bosal Postbus 168 4920 AD MADE

0.7. In the case of components and separate technical units, location and method of affixing of the EEC approval mark : on type plate

0.8. Name(s) and address(es) of assembly plants : see information document

(Annex III), item 0.8

SECTION II

Additional information 1. (where applicable)

: see Appendix I

Technical sevice responsible for 2.

carrying out the tests

: Rijksdienst v/h Wegverkeer

Testbaan Centrum Talingweg 76

8218 NX Lelystad

Date of test report 3.

4. Number of test report

Remarks (if any) 5.

6. Place

7. Date

Signature 8.

: 20-09-1995

: TC-59-94/20-155/95

: see Appendix I

: Zoetermeer

1 7 NOV. 1995 F.E. Plancius

- The index to the information package lodged with the competent authority 9. that has granted type-approval, which may be obtained on request:
 - Application form relating to Annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Testreport, as mentioned in item 4.

551-7366

Appendix I

to EEC type-approval certificate No : e4*94/20*0129*00 concerning the component type-approval of mechanical coupling devices with regard to Directive 94/20/EC

1. Additional information

1.1. Class of the type of coupling : A50-X

1.2. Categories or types of vehicles for which the device is designed or restricted

cicted : see fitting instructions

1.3. Maximum D-value : 5,96 kN

1.4. Maximum vertical load S at the coupling point : 50 kg

1.5. Maximum load U at the fifth wheel coupling point : -- ton

1.6. Maximum V-value : -- kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fixing points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles

: see fitting instructions

1.8. Information on the fitting of special towing brackets or mounting plates

: see fitting instructions

5. Remarks

: The fitting of the towbar on the vehicle must be checked according annex I nr.5.10, according the presciptions mentionend in annex VII

