

THE NETHERLANDS



EEC TYPE-APPROVAL CERTIFICATE

Communication concerning the:

- type-approval
- extension-of-type-approval
- refusal-of-type-approval
- withdrawal-of-type-approval


of a type of component (towing bracket) with regard to Directive 94/20/EC

Type-approval number: e4*94/20*0401*00

Reason for extension:

SECTION I

0.1	Make (trade name of manufacturer)	:	Bosal
0.2.	Type and general commercial description(s)	:	021441
0.3.	Means of identification of type if marked on the component	:	Approval number
0.3.1.	Location of the marking	:	on type plate
0.5.	Name and address of manufacturer	:	Bosal Postbus 168 4920 AD MADE
0.7.	In the case of components and separate technical units, location and method of affixing of the EEC approval mark	:	on type plate
0.8.	Name(s) and address(es) of assembly plants	:	see information document (Annex III), item 0.8



Type-approval number :

: e4*94/20*0401*00

SECTION II

 Additional information (where applicable)

: see Appendix I

2. Technical sevice responsible for

carrying out the tests

: RDW

Testbaan | Centrum Talingweg 76 8218 NX Lelystad

3. Date of test report

: 17-07-1996

4. Number of test report

: TCL-94/20-184/96

5. Remarks (if any)


: see Appendix I

6. Place

: Zoetermeer

7. Date

8. Signature



- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request:
 - Application form relating to Annex III and annexed drawings
 - Drawings and instructions for attachment
 - Fitting instructions
 - Testreport, as mentioned in item 4. 651-4865

Appendix I

to EEC type-approval certificate No : e4*94/20*0401*00 concerning the component type-approval of mechanical coupling devices with regard to Directive 94/20/EC

1. Additional information

1.1. Class of the type of coupling : A50-X

1.2. Categories or types of vehicles for which the device is designed or restricted

: see fitting instructions

1.3. Maximum D-value : 10.3 kN

1.4. Maximum vertical load S at the coupling point

75 kg

1.5. Maximum load U at the fifth wheel coupling point

-- ton

1.6. Maximum V-value : -- kN

1.7. Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fixing points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to

special types of vehicles :

see fitting instructions

1.8. Information on the fitting of special towing brackets or mounting plates

see fitting instructions

5. Remarks

The fitting of the towbar on the vehicle must be checked according annexI nr.5.10,according the presciptions mentionend in annex

VII

